

# **TECHNICAL DATA SHEET**

# COBALT CATALYSED SODIUM BISULPHITE SOLUTION 25% SO<sub>2</sub>

## PRODUCT DATA AND TYPICAL PROPERTIES

: NaHSO <sub>3</sub> + CoSO <sub>4</sub>
: 30 ppm approx.
: 1.33 (typical)
:0°C approx.

#### **PRODUCT SPECIFICATION**

Appearance		clear pale pink liquid
Assay	% w/w SO <sub>2</sub>	25.0 ± 0.5
	% w/w NaHSO₃	40.6 ± 0.8
pH (20℃, neat)		3.5-5.0

The product is tested using our standard analytical methods.

#### STANDARD PACKAGING

Road tankers, according to transport regulations. 1000 litre IBC, 200 and 25 litre polyethylene drums.

#### HANDLING AND STORAGE

Shelf life:	Nominally 18 months.
	Do not keep part full containers. Rapid deterioration due to oxidation will occur.
Storage Conditions:	In full, sealed containers in a cool place, out of direct sunlight, ideally in a
	warehouse. Store at 10-20 °C.
	Store away from acids and oxidising agents or products that could release acids.

#### MAIN USES

In steam boiler treatment to remove dissolved oxygen.

## FOR HANDLING INFORMATION PLEASE CONSULT THE SAFETY DATA SHEET.

Product: COBALT CATALYSED SODIUM BISULPHITE SOLUTION 25% SO2 Issue No. 8 Document Reference: PS 25SC Issue Date: Feb 2014 Page 1 of 1

Information provided on this Technical Data Sheet is believed to be accurate and is given in good faith, but it is for the Customer to satisfy itself of the suitability of the Product for its own particular purpose. Accordingly, Esseco UK Limited gives no warranty as to the fitness of the Product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that such exclusion is prevented by law. Freedom under Patent, Copyright and Designs cannot be assumed.

**ESSECO UK LIMITED**, Calder Vale Road, Wakefield, West Yorkshire, WF1 5PH, England, UK Tel +44 (0) 1924 371 919, Fax +44 (0) 1924 290 408, www.essecouk.com