

SODIUM BISULPHITE SOLUTION HP 10% SO₂

PRODUCT DATA AND TYPICAL PROPERTIES

 $\begin{array}{lll} Formula & : NaHSO_3 \\ Molecular \ weight & : 104.06 \\ Specific \ gravity \ (20\,^\circ\!\!C) & : 1.12 \ (typical) \\ Crystallisation \ temperature & : 0\,^\circ\!\!C \ approx. \end{array}$

PRODUCT SPECIFICATION

Appearance		clear pale yellow liquid
Assay	% w/w SO ₂	10.5 ± 0.5
	% w/w NaHSO₃	17.1 ± 0.8
pH (20°C, neat)		3.5-5.0
Sulphates	% Na₂SO₄	< 1.5
Iron	% as Fe	< 0.001
Heavy metals	% as Pb	< 0.001
Selenium	% as Se	< 0.00025
Arsenic	% as As	< 0.0003
Lead	% as Pb	< 0.0005
Mercury	% as Hg	< 0.0001

The product is tested using our standard analytical methods.

STANDARD PACKAGING

Road tankers, according to transport regulations.

1000 litre Intermediate bulk containers (IBCs), 200 and 25 litre polyethylene drums.

HANDLING AND STORAGE

Shelf life: Nominally 18 months.

Do not keep part full containers. Rapid deterioration due to oxidation will occur.

Storage Conditions: In full, sealed containers in a cool place, out of direct sunlight, ideally in a

warehouse. Store at 10-20 ℃.

Store away from acids and oxidising agents or products that could release acids.

MAIN USES

In water desalting plants with reverse osmosis for removing the excess of chlorine and for membrane preservation. In water treatment, in order to remove the excess of chlorine.

In chemical synthesis, in the purification of aldheydes and ketones, as catalyst, in the production of sulphonates, pesticides and herbicides, etc.

In textile and pulp & paper industry: as bleaching agent, and for removing of excess of chlorine and peroxides. In steam boiler treatment to remove dissolved oxygen.

FOR HANDLING INFORMATION PLEASE CONSULT THE SAFETY DATA SHEET.

Product: SODIUM BISULPHITE SOLUTION HP 10% SO2 Issue No. 8 Issue Date: Feb 2014

Document Reference: PS 25DD Page 1 of 1

Information provided on this Technical Data Sheet is believed to be accurate and is given in good faith, but it is for the Customer to satisfy itself of the suitability of the Product for its own particular purpose. Accordingly, Esseco UK Limited gives no warranty as to the fitness of the Product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that such exclusion is prevented by law. Freedom under Patent, Copyright and Designs cannot be assumed.